

MINIMUM TOOL SET (REQUIRED)

1/4 Inch Drive Set

Ratchet (reversible)

2" 6" 12" Extension

Six Point Socket: 1/2", 7/16", 3/8", 11/32", 5/16", 9/32", 1/4",
7/32", 3/16"

Six Point Metric Sockets: 4mm through and including 15mm

Six Point Standard Deep Sockets: 3/16", 7/32", 1/4", 9/32",
5/16", 11/32", 3/8", 7/16", 1/2"

Six Point Metric Deep Sockets: 4mm through and including 15mm
1/4 inch Swivel joint

3/8 Inch Drive Set

Ratchet (reversible)

1", 3", 6", & 12" Extension

Six Point Socket: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4",
13/16", 7/8"

Twelve Point Deep Socket: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16",
5/8", 11/16", 3/4", 13/16", 7/8", 15/16"

Six Point Flex Socket: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4"

Six Point Metric Socket: 6mm through and including 19mm

Allen Head Sockets: standard & metric

12-Point Metric Drive Deep: 6mm through and including 19mm

3/8" Universal Joint

1/2 Inch Drive Set

Breaker Bar

Ratchet (reversible)

Metric sockets: 6 point 14 mm - 24 mm

2", 3", 6", 10", & 18" Extension

Six Point Socket: 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16",
7/8", 15/16", 1", 1-1/16", 1-1/8", 1-1/4"

Combination Wrenches

5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8",
15/16", 1", 1-1/8", 1-1/4"

6mm through and including 19mm Set

Open End Box End Metric Wrenches: 19mm through and
including 30mm

Flare Nut Wrenches

1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8"

Torque Wrenches

1/2" drive: 30 ft. lb. to 250 ft. lb.

3/8" drive: 10 ft. lb. - 80 ft. lb.

Screwdrivers

9 Pieces Set of Standard and Phillips, variety of sizes

Torx Screwdrivers: T10, T15, T20, T25, T27, T30

Pliers

6" Combination Pliers

Diagonal Cutter Pliers (6")

Water Pump Pliers (10")

Needle Nose Pliers (6 3/4")

Wire Stripper

Hammers

16 oz. Ball Pein Hammer

48 oz. Ball Pein Hammer

48 oz. No Bounce Hammer (Soft Face Dead Blow)

Angle Feeler Gauge

35 blades .001-.035

Punch Set

Chisel Set

Gasket Scraper

Hacksaw (8", 10", 12" adjustable)

Tire Pressure Gauge Large truck tester 150 psi

Air Blow Gun

Tire Chuck (long for truck dual tires)

Valve Core Removal Tool

Test Light

Brass Drift

Roll Head Pry Bar

Multimeter Fluke 23 or 77

Tamper Proof Torx Drive Sockets: T-8 through T-55

20' Minimum Standard and Metric Combination Tape Measure

3/8 Inch Drive Set: Six Point Deep Impact Socket: 3/8",
7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8"

1/2" Drive Deep: 6 Pt. Impact Sockets: 1/2", 9/16", 5/8",
11/16", 3/4", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-1/4",
1-5/16"

1 Set Seal Picks

15" long Drift Punch

4piece File Set

4 piece Snap Ring Pliers

6" Caliper that reads standard and metric

1/2" Drive Air Impact Wrench

1/2" Drive Impact Flex Universal Joint

Locking Pliers 7" and 10"

3/8 to 1/2 Drive Adapter

1/2 to 3/8 Drive Adapter

Set of 3 or 4 Heavy Duty Pry Bars

Wire brush

Safety Glasses - Prescription eyeglasses -- require safety lens
and side shields

Leather Work Boots (Leather tennis shoes not acceptable)

Mechanics Gloves

Welding Gloves

Ear Protection

Welding Helmet

A tool box must be purchased 78" or smaller.